


BMR-40S-1712

1. ATX, Support up to 125W Intel® Core™ Processor Series 2 and 12/13/14th Gen. CPU
2. 4 x U-DIMM up to 128 GB DDR4 3200 MHz
3. Supports Triple display, 1 x HDMI 2.0b, 1 x DP1.4a, 1 x VGA
4. Supports 1 x PCIe x16 (Gen4), 1 x PCIe x8 (Gen4), 2 x PCIe x4 (Gen4), 1 x PCIe x4 (Gen3), 2 x PCI, 6 x COM, USB
5. Dimensions (W x H x D): 483 x 177 x 451mm



Specifications

Processor/Cache	
Processor	Support up to 125W Intel® Core™ Processor Series 2 and 12/13/14th Gen. CPU
Chipset	
Intel® Q670 chipset	
System Memory	
Memory Capacity	4 x U-DIMM up to 128 GB DDR4 3200 MHz
Expansion Slots	
PCI-Express	1 x PCIe x16 (Gen4), 1 x PCIe x8 (Gen4), 2 x PCIe x4 (Gen4), 1 x PCIe x4 (Gen3), 2 x PCI
Integrated On-Board	
SATA, M.2	4 x SATA3 (6Gb/s) 1 x M.2 (Key M, 3042/2260/2280/22110/25110) with PCIe Gen4 x4 for SSD
Network	LAN1: Intel® I225LM/I226LM with 10/100/1000/2500 Mbps, supports vPro LAN2: Intel® I225LM/I225V/I226V with 10/100/1000/2500 Mbps
Front Panel	
LED Indicators	LEDs for Power ON/OFF, HDD Activity
Drive Bays	
Peripheral Bay	3x 5.25" CD-ROM & 1x 3.5" FDD
Power Supply	
Single 350~1200W(Optional)	
Cooling System	
System Fan	2 x (92mm = 51.0CFM ea.) Hot Swap Fans
Dimensions	
W x H x D	483 x 177 x 451 mm(19.0" x 7.0" x 17.8")