


BMR-40S-1714

1. ATX, Supports up to 125W Intel® 12/13/14th Gen processors
2. 4 x U-DIMM up to 192 GB DDR5 up to 5600 MHz
3. Supports 3 displays configuration by multiple interface: VGA / DP/ HDMI
4. Supports 2 x PCIe Gen5 (Single x16 or Dual x8/x8, Riser x8/x8), 2 x PCIe Gen4 x4, 3 x PCIe Gen3 x1, 6 x COM,8, USB
5. Dimensions (W x H x D): 483 x 177 x 451mm



Specifications

Processor/Cache	
Processor	Supports up to 125W Intel® 12/13/14th Gen processors
Chipset	
Intel® Q670 chipset	
System Memory	
Memory Capacity	4 x U-DIMM slots for up to 192 GB 5600 MHz DDR5
Expansion Slots	
PCI-Express	1 x PCIe x16 (Gen5), 1 x PCIe x8 (Gen5), 2 x PCIe x4 (Gen4), 3 x PCIe x1 (Gen3)
Integrated On-Board	
SATA, M.2	8 x SATA3 (6Gb/s) 1 x M.2 (Key M, 2242/2260/2280/22110/25110) with PCIe Gen4 x4 for SSD
Network	LAN1: Intel® I226V with 10/100/1000/2500 Mbps, supports PoE LAN2: Intel® I226LM with 10/100/1000/2500 Mbps, supports vPro LAN3: Intel® I226V with 10/100/1000/2500 Mbps
Front Panel	
LED Indicators	LEDs for Power ON/OFF, HDD Activity
Drive Bays	
Peripheral Bay	3x 5.25" CD-ROM & 1x 3.5" FDD
Power Supply	
Single 350~1200W(Optional)	
Cooling System	
System Fan	2 x (92mm = 51.0CFM ea.) Hot Swap Fans
Dimensions	
W x H x D	483 x 177 x 451 mm(19.0" x 7.0" x 17.8")