

BMR-40S-H6A

1. ATX, Supports up to 125W Intel® 12/13th Gen processors
2. 2 x U-DIMM up to 64 GB DDR4 up to 3200 Mhz
3. Supports 3 displays configuration by multiple interface: VGA / HDMI / DP
4. Supports 1 x PCIe5.0 x16 slots, 1 x PCIe3.0/2.0 x16 slots(x 4 mode), 1 x PCIe3.0/2.0 x 1 slot, 4 x PCI
5. Advanced I/O and connectivity features
6. 7 years of longevity with extended product life cycles
7. Wide temperature range endurance: 0–60°C
8. Dimensions (W x H x D): 483 x 177 x 451mm



Integrated Board



Specifications

Processor/Cache	
Processor	Supports up to 125W Intel® 12th Gen processors
Chipset	
Intel® H610 chipset	
System Memory	
Memory Capacity	2 U-DIMM slots for up to 64 GB 3200 MHz DDR4
Expansion Slots	
PCI-Express	1 x PCIe 5.0 x16 slot 1 x PCIe 3.0/2.0 x16 slot (x4 mode) 1 x PCIe 3.0/2.0 x1 slot 4 x PCI slot
Integrated On-Board	
SATA, M.2	4 x SATA Gen 3.0, up to 6Gb/s 1 x M.2 Socket 3 with M key, type 2242/2260/2280(SATA / PCIe x 1 mode)
Network	1 x Intel® I219V 1 x Intel® I210AT
Front Panel	
LED Indicators	LEDs for Power ON/OFF, HDD Activity
Drive Bays	
Peripheral Bay	3x 5.25" CD-ROM & 1x 3.5" FDD
Power Supply	
Single 350~1200W (Option)	
Cooling System	
System Fan	2x (92mm = 51.0CFM ea.) Hot Swap Fans
Dimensions	
W x H x D	483 x 177 x 451mm (19.0" x 7.0" x 17.8")