

BMR-40S-Q6M

1. Micro-ATX, Supports up to 65W Intel® 12/13th Gen processors
2. 2 x U-DIMM up to 64 GB DDR4 up to 3200 MHz
3. Supports 3 displays configuration by multiple interface: VGA / DP/ HDMI1 / HDMI2
4. Supports 1 x PCIe5.0 x16 slot, 1 x PCIe3.0/2.0 x4 slot(x1 speed), 2 x PCI,1 x Mini PCIe,6 x COM,9 x USB
5. 7 years of longevity with extended product life cycles
6. Dimensions (W x H x D): 483 x 177 x 451mm



Integrated Board



Specifications

Processor/Cache	
Processor	Supports up to 65W Intel® 12th Gen processors
Chipset	
Intel® H610 chipset	
System Memory	
Memory Capacity	2 U-DIMM slots for up to 64GB 3200 MHz DDR4
Expansion Slots	
PCI-Express	1 x PCIe 4.0 x16 Slot
Integrated On-Board	
SATA, M.2	4 x SATA Gen 3.0, up to 6Gb/s *No.4 SATA port shared with M.2 1 x M.2 E key, Type 2230 for WIFI/ BT device (PCIe & CNVi) 1 x M.2 M key, Type 2242/ 2260/ 2280 (PCIe x4/ SATA mode)
Network	1 x Intel® I210at 1 x Intel® i219V
Font Panel	
LED Indicators	LEDs for Power ON/OFF, HDD Activity
Drive Bays	
Peripheral Bay	3x 5.25" CD-ROM & 1x 3.5" FDD
Power Supply	
Single 350~1200W (Option)	
Cooling System	
System Fan	2x (92mm = 51.0CFM ea.) Hot Swap Fans
Dimensions	
W x H x D	483 x 177 x 451mm (19.0" x 7.0" x 17.8")