

BMS 2125-620(R)

1. 2U Rackmount server chassis series with 620mm depth
2. Serverboard supports up to standard EEB 12"x13", backward supports to CEB and below
3. Supports default 7x low-profile or optional 3x full-height full-length PCIe cards
4. Front 25x 2.5" hot-swap HDDs and rear 2x2.5" hot-swap HDDs
5. High-performance 4x 8038 cooling fans with anti-vibration mechanism
6. Smart system fan controlled by intelligent temperature management
7. 12Gb/s SAS Expander backplane with SGPIO, compatible with SAS and SATA HDDs



Specifications

Chassis Form Factor	2U Rackmount
Serverboard	EEB(12"x13"), CEB(12"x10.5"), ATX (12"x9.6") and micro ATX (9.6"x9.6")
PSU Form Factor	2U Single or 1+1 Redundant (CRPS)
Backplane SGPIO	Supports
HDD Backplane	25-port 2.5" 12Gb/s SAS Expander backplane 2-port 2.5" 12Gb/s SAS backplane (option)
HDD Drive Hot-swap	Front 25 x 2.5" Hot-swap HDDs Rear 2 x 2.5" Hot-swap HDDs (option)
Cooling Fans	Default 4 x 8038 Hot-swap middle fans
Temperature Control	Supports system smart fan control by Server board
Expansion Slots	Default 7x low-profile PCIe Cards or optional 3x full-height PCIe Cards
Indicators	2x USB2.0, 1x Power Switch, 1x Reset, 1x Power LED, 1x HDD LED, 2x LAN Indicators
Metal Thickness	1mm SGCC
Net Weight	10.5 Kgs
Chassis Dimensions (HxWxD)	88mm x 444mm x 620mm