

BMS 4136-670(R)

1. 4U Rackmount server chassis series with 670 mm depth
2. Serverboard supports up to standard EEB 12"x13" and backward supports to CEB
3. Supports 7 x full height and full length PCIe cards
4. Front 24 x3.5" hot swap HDDs and rear 12 x 3.5" hot-swap HDDs (2.5" HDD compatible) and rear 2 x2.5" hot swap HDDs
5. High-performance 8 x 8038 cooling fans with anti-vibration mechanism
6. Smart system fan controlled by intelligent temperature management
7. Supports 2U Single PSU or 1+1 Redundant PSU
8. 12Gb/s SAS passive backplane with SGPIO, compatible with SAS and SATA HDDs



Specifications

Chassis Form Factor	4U Rackmount
Serverboard	EEB(12"x13"), CEB(12"x10.5"), ATX (12"x9.6") and micro ATX (9.6"x9.6")
PSU Form Factor	2U Single or 1+1 Redundant (CRPS)
Backplane SGPIO	Supports
HDD Backplane	24-port 3.5" 12Gb/s SAS Expander backplane 12-port 3.5" 12Gb/s SAS Expander backplane 2-port 2.5" 12Gb/s SAS passive backplane (option)
HDD Drive Hot-swap	Front 24 x 3.5" Hot-swap HDDs (2.5" HDD compatible) Rear 12 x 3.5" Hot-swap HDDs (2.5" HDD compatible) Rear 2 x 2.5" Hot-swap HDDs (option)
Cooling Fans	Default 8x8038 Hot-swap middle fans
Temperature Control	Supports system smart fan control by Server board
Expansion Slots	Default 7x low-profile PCIe Cards or optional 3x full-height PCIe Cards support
Indicators	2x USB2.0, 1x Power Switch, 1x Reset, 1x Power LED, 1x HDD LED, 2x LAN Indicators
Metal Thickness	1mm SGCC
Net Weight	22.5 Kgs
Chassis Dimensions (HxWxD)	177mm x 444mm x 670mm