

Nuvo-5608VR Series

Intel® 6th-Gen Core™ i7/i5 Fanless Surveillance System with 8x PoE+, DIO, CAN Bus and 2x 3.5" HDD Accommodation Supporting RAID 0/1



CE FC

Key Features

- Supports Intel® 6th-Gen Core™ i7/ i5/ i3 LGA1151 socket-type CPU
- 8x 802.3at PoE+ ports and 2x GbE ports
- 2x 3.5" HDD accommodation, support RAID 0/1 with over 24 TB capacity
- Dedicated HDD heat-spreader for optimized thermal performance
- 4x full-size mini-PCIe sockets with SIM support
- 4-CH isolated DI and 4-CH isolated DO
- 1x CAN 2.0 port
- 8~35V wide-range DC input with built-in ignition power control

Introduction

Nuvo-5608VR is Neosys' latest fanless surveillance system designed for real-time video analysis and streaming. It incorporates 6th-Gen Core™ i CPU, IP camera connectivity and massive storage capacity for emerging intelligent surveillance/ security applications.

Featuring eight Gigabit PoE+ ports, Nuvo-5608VR provides sufficient bandwidth to collect high-definition video streams from IP cameras, while its 6th-Gen Core™ i7 CPU is capable of performing real-time video analytics. It accommodates two 3.5" hard drives with RAID 0/1 configuration to support more than 24 TB storage capacity for recording 8-CH, 1080p@H.264 video for over 3 months.


Neosys' patented damping-bracket is shipped with Nuvo-5608VR to protect the system against vibration in harsh environmental conditions.

Being a rugged surveillance platform, Nuvo-5608VR is equipped with dedicated HDD heat-spreaders to maintain adequate HDD operating temperature and along with extra features such as DIO, CAN bus and ignition control, Nuvo-5608VR is the perfect fit for both stationary and mobile surveillance applications.


Specifications

System Core		Expansion Bus	
Processor	Supports 6th-Gen Intel® Core™ i7/ i5/ i3 LGA1151 CPU Intel® Core™ i7-6700 (8M Cache, 3.4/ 4.0 GHz, 65W TDP) Intel® Core™ i5-6500 (6M Cache, 3.2/ 3.6 GHz, 65W TDP) Intel® Core™ i3-6100 (3M Cache, 3.7 GHz, 51W TDP) Intel® Core™ i7-6700TE (8M Cache, 2.4/ 3.4 GHz, 35W TDP) Intel® Core™ i5-6500TE (6M Cache, 2.3/ 3.3 GHz, 35W TDP) Intel® Core™ i3-6100TE (4M Cache, 2.7 GHz, 35W TDP)	mini-PCIe	1x full-size mini-PCIe socket with panel-accessible SIM socket 1x full-size mini-PCIe socket with internal SIM socket (mux with mSATA) 2x full-size mini-PCIe sockets (USB signals only) with internal SIM sockets
Chipset	Intel® Q170 Platform Controller Hub	Power Supply	DC Input 1x 3-pin pluggable terminal block for 8~35VDC DC input
Graphics	Integrated Intel® HD Graphics 530	Remote Ctrl. & Status Output	1x 10-pin (2x5) wafer connector for remote on/off control and status LED output
Memory	Up to 32 GB DDR4-2133 SDRAM by two SODIMM sockets	Mechanical	Dimension 240 mm (W) x 225 mm (D) x 98 mm (H)
AMT	Supports AMT 11.0	Weight	3.5 kg
TPM	Supports TPM 2.0	Mounting	Neosys' patented damping bracket
I/O Interface		Environmental	Operating Temperature -25°C ~ 70°C (with mSATA/SSD) ** -10°C ~ 60°C (with 3.5" HDD) **/****
Ethernet port	2x Gigabit Ethernet ports by Intel® I219 and I210	Storage Temperature	-40°C ~ 85°C
PoE+	8x IEEE 802.3at (25.5W) Gigabit PoE+ ports by Intel® I210, 120W total power budget*	Humidity	10%~90%, non-condensing
USB	4x USB 3.0 ports via native XHCI controller 4x USB 2.0 ports	Vibration	Operating, 1 Grms, 5-500 Hz, 3 Axes (w/ HDD and damping bracket installed, according to IEC60068-2-64)
Video Port	1x stacked VGA + DVI-D connector 2x DisplayPort connectors, supporting 4K2K resolution	Shock	Operating, 30 Grms, Half-sine 11 ms Duration (w/ HDD and damping bracket installed, according to IEC60068-2-27)
Serial Port	2x software-programmable RS-232/ 422/ 485 ports (COM1 & COM3) 1x RS-232 port (COM2)	EMC	CE/FCC Class A, according to EN 55022 & EN 55024
Isolated DIO	4x isolated DI and 4x isolated DO	* The total power budget for Nuvo-5608VR is related to input voltage. 120W total budget is available with 24 VDC input. When 12 VDC input is applied, the total power budget is limited to 100W. ** Operating temperature is verified with 100% CPU loading and 100% HDD loading applied using Passmark® BurnInTest 8.0. For detail testing criteria, please contact Neosys Technology. *** Depending on the HDD selected, users may encounter performance degradation in sequential disk write at low/high ambient temperature. No data integrity issue was observed in -10°C ~ 60°C operating temperature range.	
CAN	1x CAN 2.0 port		
Audio	1x mic-in and 1x speaker-out		
Storage Interface			
SATA HDD	2x internal SATA port for 3.5" HDD installation, supporting RAID 0/1		
mSATA	1x full-size mSATA port (mux with mini-PCIe)		

Appearance



Dimensions



Ordering Information

Model No.	Product Description
Nuvo-5608VR	Intel® 6th-Gen Skylake Core™ i7 /i5/ i3 Fanless Surveillance System with 8x PoE+ Ports, DIO, CAN Bus and 2x 3.5" HDD RAID

Optional Accessories

- 160W, 8A/ 20V AC/ DC power adapter
- 280W, 11.6A/ 24V AC/ DC power adapter