

BMS 1104-670(R)

1. 1U Rackmount server chassis series with 670mm depth
2. Serverboard support up to standard EEB 12"x13", backward supports to CEB and below
3. Supports 1x full-height full-length PCIe cards
4. Front 4x3.5" hot-swap HDDs(2.5" HDD compatible) and 2x2.5" internal HDDs
5. High-performance 4x 4028 cooling fans with anti-vibration mechanism and optional up to 6x 4056 middle fans
6. Smart system fan controlled by intelligent temperature management
7. 12Gb/s SAS passive backplane with SGPIO, compatible with SAS and SATA HDDs
- 8. Supports 1U Single PSU or 1+1 Redundant PSU**



Specifications

Chassis Form Factor	1U Rackmount
Serverboard	EEB(12"x13"), CEB(12"x10.5"), ATX (12"x9.6") and micro ATX (9.6"x9.6")
PSU Form Factor	1U Single or 1+1 Redundant
Backplane SGPIO	Supports
HDD Backplane	4-port 12Gb/s SAS passive backplane
HDD Drive Hot-swap	Supports SAS and SATA HDD, Front 4 x 3.5" Hot-swap HDDs (2.5" HDD compatible); Internal 2 x 2.5" HDDs
Cooling Fans	Default 4 x 4028 middle fans (Max. 6 x 4056 by option)
Temperature Control	Supports system smart fan control by Server board
Expansion Slots	Default 1x full-height PCIe cards support
Indicators	2x USB2.0, 1x Power Switch, 1x Reset, 1x Power LED, 1x HDD LED, 2x LAN Indicators
Metal Thickness	1mm SGCC
Net Weight	7.3KG
Chassis Dimensions (HxWxD)	670mm x 433mm x 43mm